
## **SDR 26 HWS GASKETED BELL GRAVITY APPLICATIONS**

- A. BELL END ACCEPTS PIPE WITH SDR 26, ASTM D3034
  OR EQUIVALENT O.D. SPECIFICATION IN 8", 10", 12",
  15", 18", 21", 24", 27", AND 30" SIZES
  (FOR 4" AND 6" SIZES, REFER TO FATBOY
  SPECIFICATIONS)
- B. CURVATURE VARIES WITH MAINLINE DIAMETERS.
- C. SPIGOT END PVC SDR 26, ASTM D3034 DIAMETERS: 8", 10", 12", 15", 18", 21", 24", 27" AND 30"



## MATERIALS

PVC SDR 26 ASTM D3034 ASTM F477 BAND SS #301 SCREW SS #305 HOUSING SS #301 ASTM F477

PARI	PARI NAME		
1	HUB ADAPTOR		
2	RUBBER GASKET		
3	SECURING CLAMP*		
4	RUBBER SLEEVE (AVAILABLE IN NITRILE AND EPDM BY SPECIAL ORDER)		
4A	UPPER SEGMENT**		
4B	LOWER SEGMENT***		

<sup>\*</sup> OPTIONAL: #316 STAINLESS STEEL BAND, SCREW AND HOUSING

<sup>\*\*\*</sup> WILL NOT APPEAR ON RUBBER SLEEVES FOR CONCRETE OR CLAY PIPE

n)
n)
m)
ım)
m)
m)
m)
n)
nm)

NOTE: RECOMMENDED METHOD OF CUTTING HOLE IS WITH HOLE SAW FOR PVC AND OTHER PLASTICS, AND DIAMOND BIT FOR CONCRETES, CLAY, FRP AND D.I. (SEE INSTALLATION INSTRUCTIONS. HOLE SAWS ARE AVAILABLE FOR PURCHASE OR RENT.)



INSERTA TEE | PO BOX 714 CORNELIUS, OR 97113 PH:(503) 357-2110 FAX:(503) 359-5417 SALES@INSERTATEE.COM

## SDR 26 HWS GASKETED BELL GRAVITY APPLICATION SPECIFICATIONS

	SCALE:	NTS
	DATE:	7/30/13
	DRAWN BY:	JJC

THIS PRINT DISCLOSES SUBJECT MATTER IN WHICH INSERTA-TEE HAS PROPRIETARY RIGHTS. THE RECEIPT OR POSSESSION OF THIS PRINT DOES NOT CONFER, TRANSFER, OR LICENSE THE USE OF THE DESIGN OR TECHNICAL INFORMATION SHOWN HEREIN REPRODUCTION OF THIS PRINT OR ANY INFORMATION CONTAINED HEREIN, OR MANUFACTURE OF ANY ARTICLE HEREFROM, FOR THE DISCLOSURE TO OTHERS IS FORBIDDEN, EXCEPT BY SPECIFIC WRITTEN PERMISSION FROM INSERTA-TEE.

<sup>\*\*</sup> DISTANCE BETWEEN 4A AND 4B WILL VARY BY PRODUCT TYPE